



SealXpert® Products

MARINE CATALOGUE

2017



IMPA CODE REFERENCE

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE	IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
232441	SEALXPRT HATCH COVER TAPE	4	251235	SEALXPRT ANTI-SLIP FLOOR COATING	7
232442	SEALXPRT HATCH COVER TAPE	4	251236	SEALXPRT ANTI-SLIP FLOOR COATING	7
232443	SEALXPRT HATCH COVER TAPE	4	251241	SEALXPRT ANTI-SLIP FLOOR COATING	7
232445	SEALXPRT HATCH COVER TAPE	4	251242	SEALXPRT ANTI-SLIP FLOOR COATING	7
232446	SEALXPRT HATCH COVER TAPE	4	251243	SEALXPRT ANTI-SLIP FLOOR COATING	7
232448	SEALXPRT HATCH COVER TAPE	4	251244	SEALXPRT ANTI-SLIP FLOOR COATING	7
232449	SEALXPRT HATCH COVER TAPE	4	251245	SEALXPRT ANTI-SLIP FLOOR COATING	7
232451	SEALXPRT HATCH COVER TAPE	4	251246	SEALXPRT ANTI-SLIP FLOOR COATING	7
232452	SEALXPRT HATCH COVER TAPE	4	251247	SEALXPRT ANTI-SLIP FLOOR COATING	7
232453	SEALXPRT HATCH COVER TAPE	4	251471	SEALXPRT COMMON MARINE PUTTY	6
232454	SEALXPRT HATCH COVER TAPE	4	251472	SEALXPRT COMMON MARINE PUTTY	6
232455	SEALXPRT HATCH COVER TAPE	4	251473	SEALXPRT COMMON MARINE PUTTY	6
232456	SEALXPRT HATCH COVER TAPE	4	251476	SEALXPRT COMMON MARINE PUTTY	6
232457	SEALXPRT HATCH COVER TAPE	4	251477	SEALXPRT COMMON MARINE PUTTY	6
232458	SEALXPRT HATCH COVER TAPE	4	251481	SEALXPRT COMMON MARINE PUTTY	6
232459	SEALXPRT HATCH COVER TAPE	4	251482	SEALXPRT COMMON MARINE PUTTY	6
232460	SEALXPRT HATCH COVER TAPE	4	251611	SEALXPRT ANTI-SLIP FLOOR COATING	7
232461	SEALXPRT HATCH COVER STRIPS	4	251612	SEALXPRT ANTI-SLIP FLOOR COATING	7
232462	SEALXPRT HATCH COVER STRIPS	4	251621	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7
232463	SEALXPRT HATCH COVER STRIPS	4	251701	SEALXPRT ANTI-SLIP FLOOR COATING	7
232464	SEALXPRT HATCH COVER TAPE	4	251702	SEALXPRT ANTI-SLIP FLOOR COATING	7
232465	SEALXPRT HATCH COVER TAPE	4	251703	SEALXPRT ANTI-SLIP FLOOR COATING	7
232466	SEALXPRT HATCH COVER TAPE	4	251704	SEALXPRT ANTI-SLIP FLOOR COATING	7
232467	SEALXPRT HATCH COVER STRIPS	4	251705	SEALXPRT WR204 WEAR RESISTANT COATING	6
232468	SEALXPRT HATCH COVER STRIPS	4	251707	SEALXPRT MC38 MARINE CHOCK	7
232469	SEALXPRT HATCH COVER STRIPS	4	251710	SEALXPRT MC38 MARINE CHOCK	7
232470	SEALXPRT HATCH COVER STRIPS	4	251711	SEALXPRT WR204 WEAR RESISTANT COATING	6
232472	SEALXPRT HATCH COVER STRIPS	4	251712	SEALXPRT WR204 WEAR RESISTANT COATING	6
232473	SEALXPRT HATCH COVER STRIPS	4	251713	SEALXPRT WR204 WEAR RESISTANT COATING	6
232474	SEALXPRT HATCH COVER STRIPS	4	330287	WRAP SEAL PLUS LIFEBOAT REPAIR KIT 1	10
232475	SEALXPRT HATCH COVER STRIPS	4	330288	WRAP SEAL PLUS LIFEBOAT REPAIR KIT 2	10
232476	SEALXPRT HATCH COVER STRIPS	4	330289	WRAP SEAL PLUS LIFEBOAT REPAIR KIT 3	10
232477	SEALXPRT HATCH COVER STRIPS	4	430311	SEALXPRT HATCH COVER STRIPS	4
232478	SEALXPRT HATCH COVER STRIPS	4	450336	SEALXPRT MOLY GREASE	11
232479	SEALXPRT HATCH COVER STRIPS	4	450337	SEALXPRT MOLY GREASE	11
232480	SEALXPRT HATCH COVER STRIPS	4	450346	SEALXPRT MOLY GREASE	11
250822	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450347	SEALXPRT MOLY GREASE	11
250824	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450419	SEALXPRT THREAD SEALANT TS577	8
251012	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450420	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
251014	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450451	SEALXPRT MOLY M77 PASTE	11
251034	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450452	SEALXPRT MOLY M77 PASTE	11
251035	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450461	SEALXPRT HI-SPEED MOLY GREASE	11
251043	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450462	SEALXPRT HI-SPEED MOLY GREASE	11
251044	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450463	SEALXPRT HI-SPEED MOLY GREASE	11
251054	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450464	SEALXPRT HI-SPEED MOLY GREASE	11
251055	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450465	SEALXPRT HI-SPEED MOLY GREASE	11
251061	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450466	SEALXPRT HI-SPEED MOLY GREASE	11
251062	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450471	SEALXPRT HI-TEMP MOLY GREASE	11
251074	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450472	SEALXPRT HI-TEMP MOLY GREASE	11
251075	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450473	SEALXPRT HI-TEMP MOLY GREASE	11
251096	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450474	SEALXPRT HI-TEMP MOLY GREASE	11
251097	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450475	SEALXPRT HI-TEMP MOLY GREASE	11
251084	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450476	SEALXPRT HI-TEMP MOLY GREASE	11
251085	SEALXPRT ANTI-CORROSIVE EPOXY COATING	7	450481	SEALXPRT MOLY GREASE	11
251231	SEALXPRT ANTI-SLIP FLOOR COATING	7	450482	SEALXPRT MOLY GREASE	11
251232	SEALXPRT ANTI-SLIP FLOOR COATING	7	450483	SEALXPRT MOLY GREASE	11
251233	SEALXPRT ANTI-SLIP FLOOR COATING	7	450501	SEALXPRT MOLY Z POWDER	11
251234	SEALXPRT ANTI-SLIP FLOOR COATING	7	450502	SEALXPRT MOLY Z POWDER	11

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
450503	SEALXPRT MOLY Z POWDER	11
450504	SEALXPRT MOLY MICRO POWDER	11
450505	SEALXPRT MOLY MICRO POWDER	11
450511	SEALXPRT MOLY G-N PASTE	11
450512	SEALXPRT MOLY G-N PASTE	11
450513	SEALXPRT MOLY G-N PASTE	11
450514	SEALXPRT SP50 MOLY G-RAPID	10/11
450515	SEALXPRT MOLY M77 PASTE	11
450516	SEALXPRT MOLY M77 PASTE	11
450517	SEALXPRT MOLY M77 PASTE	11
450518	SEALXPRT MOLY M77 PASTE	11
450519	SEALXPRT MOLY M77 PASTE	11
450520	SEALXPRT SP50 MOLY G-RAPID	10/11
450521	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450522	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450526	SEALXPRT MOLY GREASE	11
450527	SEALXPRT MOLY GREASE	11
450534	SEALXPRT M	11
450535	SEALXPRT M	11
450536	SEALXPRT M-30	11
450551	SEALXPRT 111 SILICONE GREASE	11
450553	SEALXPRT 111 SILICONE GREASE	11
450564	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450565	SEALXPRT SP50 MOLY G-RAPID	10/11
450566	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450567	SEALXPRT MOLY GREASE	11
450568	SEALXPRT MOLY GREASE	11
450571	SEALXPRT HI-SPEED MOLY GREASE	11
450572	SEALXPRT HI-SPEED MOLY GREASE	11
450573	SEALXPRT M	11
450574	SEALXPRT M	11
450578	SEALXPRT SP50 MOLY G-RAPID	10/11
450581	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450583	SEALXPRT SP20 CLEANER AND DEGREASER	10
450584	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450586	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450587	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450591	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450592	SEALXPRT SP10 CONTACT CLEANER	10
450594	SEALXPRT MOLY G-N PASTE	11
450595	SEALXPRT MOLY G-N PASTE	11
450598	SEALXPRT NICKEL ANTI-SEIZE	11
450599	SEALXPRT NICKEL ANTI-SEIZE	11
450606	SEALXPRT SP50 MOLY G-RAPID	10/11
450607	SEALXPRT SP60 SILICONE GREASE	10
450608	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450609	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450616	SEALXPRT SP20 CLEANER AND DEGREASER	10
450617	SEALXPRT SP10 CONTACT CLEANER	10
450618	SEALXPRT SP10 CONTACT CLEANER	10
450619	SEALXPRT SP10 CONTACT CLEANER	10
450621	SEALXPRT SP10 CONTACT CLEANER	10
450622	SEALXPRT SP20 CLEANER AND DEGREASER	10
450631	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450633	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450634	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450635	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450636	SEALXPRT NICKEL ANTI-SEIZE	11

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
450637	SEALXPRT NICKEL ANTI-SEIZE	11
450638	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450639	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450640	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450641	SEALXPRT SP50 MOLY G-RAPID	10/11
450645	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450649	SEALXPRT SP10 CONTACT CLEANER	10
450650	SEALXPRT SP10 CONTACT CLEANER	10
450651	SEALXPRT 111 SILICONE GREASE	11
450653	SEALXPRT MOLY GREASE	11
450641	SEALXPRT SP50 MOLY G-RAPID	10/11
450661	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450662	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450665	SEALXPRT NICKEL ANTI-SEIZE	11
450666	SEALXPRT NICKEL ANTI-SEIZE	11
450681	SEALXPRT NICKEL ANTI-SEIZE	11
450682	SEALXPRT NICKEL ANTI-SEIZE	11
450683	SEALXPRT C1000 COPPER ANTI-SEIZE COMPOUND	11
450691	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450692	SEALXPRT MOLY 1000 ANTI-SEIZE COMPOUND	11
450693	SEALXPRT NICKEL ANTI-SEIZE	11
450694	SEALXPRT NICKEL ANTI-SEIZE	11
450671	SEALXPRT MOLY M77 PASTE	11
450672	SEALXPRT MOLY M77 PASTE	11
450702	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450703	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450704	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450705	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450709	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450731	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450732	SEALXPRT HI-TEMP MOLY GREASE	11
450756	SEALXPRT 111 SILICONE GREASE	11
450757	SEALXPRT 111 SILICONE GREASE	11
450758	SEALXPRT 111 SILICONE GREASE	11
450759	SEALXPRT 111 SILICONE GREASE	11
450761	SEALXPRT HI-TEMP MOLY GREASE	11
450762	SEALXPRT HI-TEMP MOLY GREASE	11
450763	SEALXPRT HI-TEMP MOLY GREASE	11
450764	SEALXPRT HI-TEMP MOLY GREASE	11
450801	SEALXPRT SP20 CLEANER AND DEGREASER	10
450802	SEALXPRT SP20 CLEANER AND DEGREASER	10
450803	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450804	SEALXPRT SP10 CONTACT CLEANER	10
450805	SEALXPRT SP10 CONTACT CLEANER	10
450808	SEALXPRT SP10 CONTACT CLEANER	10
450811	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450812	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450813	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450814	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450821	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450822	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450823	SEALXPRT SP40 MULTIPURPOSE LUBRICANT	10
450827	SEALXPRT SP60 SILICONE GREASE	10
450828	SEALXPRT SP60 SILICONE GREASE	10
450829	SEALXPRT SP50 MOLY G-RAPID	10/11
450830	SEALXPRT SP60 SILICONE GREASE	10
450846	SEALXPRT SP50 MOLY G-RAPID	10/11
450847	SEALXPRT SP50 MOLY G-RAPID	10/11

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
450901	SEALXPRT SP10 CONTACT CLEANER	10
450902	SEALXPRT SP10 CONTACT CLEANER	10
450915	SEALXPRT SP30 ZINC COLD-GALVANISING (BRIGHT)	10
450926	SEALXPRT SP60 SILICONE GREASE	10
614170	WRAP CLAMP WC1 DN50 X 80MM	2
614171	WRAP CLAMP WC1 DN65 X 140MM	2
614172	WRAP CLAMP WC1 DN80 X 200MM	2
614173	WRAP CLAMP WC1 DN100 X 200MM	2
614174	WRAP CLAMP WC1 DN125 X 200MM	2
614175	WRAP CLAMP WC1 DN150 X 200MM	2
614176	WRAP CLAMP WC1 DN200 X 255MM	2
614177	WRAP CLAMP WC1 DN250 X 255MM	2
614178	WRAP CLAMP WC1 DN300 X 255MM	2
614180	WRAP CLAMP WC1 DN50 X 80MM	2
614181	WRAP CLAMP WC1 DN65 X 140MM	2
614182	WRAP CLAMP WC1 DN80 X 200MM	2
614183	WRAP CLAMP WC1 DN100 X 200MM	2
614184	WRAP CLAMP WC1 DN125 X 200MM	2
614185	WRAP CLAMP WC1 DN150 X 200MM	2
614186	WRAP CLAMP WC1 DN200 X 255MM	2
614187	WRAP CLAMP WC1 DN250 X 255MM	2
614188	WRAP CLAMP WC1 DN300 X 255MM	2
795510	SEALXPRT SP10 CONTACT CLEANER	10
795511	SEALXPRT SP10 CONTACT CLEANER	10
811701	WRAP SEAL PLUS GLASS CLOTH	3
811702	WRAP SEAL PLUS GLASS CLOTH	3
811703	WRAP SEAL PLUS GLASS CLOTH	3
811710	WRAP SEAL PLUS GLASS TAPE	3
811711	WRAP SEAL PLUS GLASS TAPE	3
811712	WRAP SEAL PLUS GLASS TAPE	3
811713	WRAP SEAL PLUS GLASS TAPE	3
811714	WRAP SEAL PLUS GLASS TAPE	3
811715	WRAP SEAL PLUS GLASS TAPE	3
812155	SEALXPRT RV598A BLACK RTV SILICONE	11
812156	SEALXPRT RV598 BLACK RTV SILICONE	11
812171	SEALXPRT MAINTENANCE AND REPAIR KIT 5	10
812173	WRAP SEAL WS0206	1
812174	WRAP SEAL WS0212	1
812175	SEALXPRT ULTRA SEALING TAPE	1
812176	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812177	SEALXPRT PS103 ALUMINIUM EPOXY PUTTY	5
812178	SEALXPRT PS105 STAINLESS STEEL EPOXY PUTTY	5
812179	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812180	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812181	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812182	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812183	SEALXPRT WR204 WEAR RESISTANT COATING	6
812184	SEALXPRT WR204 WEAR RESISTANT COATING	6
812185	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812186	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812187	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812188	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812190	SEAL STIC SS102 STEEL EPOXY STICK	4
812191	SEAL STIC SS102 STEEL EPOXY STICK	4
812193	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812195	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812197	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812198	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
812199	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812201	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812202	SEAL STIC SS102 STEEL EPOXY STICK	4
812203	SEALXPRT PS104 BRONZE EPOXY PUTTY	5
812204	SEAL STIC SS104 BRONZE EPOXY STICK	4
812207	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812209	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812211	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812212	SEALXPRT PS104 BRONZE EPOXY PUTTY	5
812216	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812220	SEAL STIC SS102 STEEL EPOXY STICK	4
812222	WRAP SEAL PLUS GLASS TAPE	3
812223	WRAP SEAL PLUS GLASS TAPE	3
812224	WRAP SEAL PLUS GLASS TAPE	3
812225	WRAP SEAL PLUS GLASS TAPE	3
812230	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812231	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812232	FLAMECEASE FIRE PROTECTION COATING	12
812234	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812235	SEALXPRT ENGINEER'S REPAIR KIT A	10
812237	SEALXPRT ENGINEER'S REPAIR KIT C	10
812238	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812239	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812240	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812241	SEALXPRT PS110 TITANIUM EPOXY PUTTY	5
812242	SEALXPRT PS110 TITANIUM EPOXY PUTTY	5
812243	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812245	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812246	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812247	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812248	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812249	SEALXPRT PL104 RUBBER REPAIR LIQUID	5
812251	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812252	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812253	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812256	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812257	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812262	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812266	SEALXPRT PS103 ALUMINIUM EPOXY PUTTY	5
812267	SEALXPRT PS103 ALUMINIUM EPOXY PUTTY	5
812271	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812272	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812281	SEALXPRT WR204 WEAR RESISTANT COATING	6
812286	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812290	SEALXPRT PS104 BRONZE EPOXY PUTTY	5
812292	SEALXPRT PS105 STAINLESS STEEL EPOXY PUTTY	5
812293	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812294	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812298	SEALXPRT REPAIR PATCH	2
812301	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812302	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812306	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812308	SEAL STIC SS102 STEEL EPOXY STICK	4
812310	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812312	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812315	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812321	WRAP SEAL PLUS GLASS CLOTH	3
812322	WRAP SEAL PLUS GLASS CLOTH	3

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
812323	WRAP SEAL PLUS GLASS TAPE	3
812324	WRAP SEAL PLUS GLASS TAPE	3
812325	WRAP SEAL PLUS GLASS TAPE	3
812330	WRAP SEAL PLUS REPAIR KIT COMPLETE	10
812331	SEALXPRT MAINTENANCE AND REPAIR KIT 1	10
812332	SEALXPRT MAINTENANCE AND REPAIR KIT 2	10
812333	SEALXPRT MAINTENANCE AND REPAIR KIT 3	10
812334	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812335	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812336	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812337	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812338	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812339	WRAP SEAL PLUS GLASS TAPE	3
812340	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812341	SEALXPRT MAINTENANCE AND REPAIR KIT 4	10
812342	SEAL STIC SS102 QUICK CURE STEEL EPOXY STICK	4
812343	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812344	SEALXPRT PIPE TAPES	1
812345	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812346	SEALXPRT PS108 HI-TEMP EPOXY PUTTY	5
812347	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812348	SEALXPRT PIPE TAPES	1
812351	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812352	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812353	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812355	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812356	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812357	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812358	SEALXPRT PS103 ALUMINIUM EPOXY PUTTY	5
812359	SEALXPRT PS105 STAINLESS STEEL EPOXY PUTTY	5
812361	WRAP SEAL WS0205	1
812362	WRAP SEAL WS0212	1
812363	WRAP SEAL WS0412	1
812364	WRAP SEAL WS0206	1
812365	WRAP SEAL WS0309	1
812367	SEALXPRT PIPE REPAIR KIT	1
812371	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812372	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812375	SEAL STIC SS106 UNDERWATER EPOXY STICK	4
812377	SEALXPRT WR204 WEAR RESISTANT COATING	6
812378	SEALXPRT WR204 WEAR RESISTANT COATING	6
812381	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812382	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812385	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812386	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812387	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812388	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812391	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812392	SEALXPRT PL102 STEEL REPAIR LIQUID	5
812393	SEALXPRT PL104 RUBBER REPAIR LIQUID	5
812394	SEALXPRT PL104 RUBBER REPAIR LIQUID	5
812395	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812396	SEALXPRT PS109 SUPERMETAL EPOXY PUTTY	5
812397	SEALXPRT PS107 5 MINUTES EPOXY PUTTY	5
812398	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812399	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812401	SEALXPRT MOLY MICRO POWDER	11
812402	SEALXPRT MOLY MICRO POWDER	11

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
812403	SEALXPRT MOLY MICRO POWDER	11
812406	SEALXPRT MOLY Z POWDER	11
812407	SEALXPRT MOLY Z POWDER	11
812408	SEALXPRT MOLY Z POWDER	11
812411	SEALXPRT MOLY G-N PASTE	11
812412	SEALXPRT MOLY G-N PASTE	11
812413	SEALXPRT MOLY G-N PASTE	11
812420	SEALXPRT THREAD SEALANT TS577	8
812451	WRAP SEAL WS0205	1
812452	WRAP SEAL WS0309	1
812453	WRAP SEAL WS0412	1
812454	WRAP SEAL PLUS FIBERGLASS REPAIR TAPE	1
812455	WRAP SEAL PLUS FIBERGLASS REPAIR TAPE	1
812457	WRAP SEAL PLUS FIBERGLASS REPAIR TAPE	1
812458	WRAP SEAL PLUS FIBERGLASS REPAIR TAPE	1
812471	SEALXPRT PETRO TAPE	3
812472	SEALXPRT PETRO TAPE	3
812473	SEALXPRT PETRO TAPE	3
812474	SEALXPRT PETRO TAPE	3
812475	SEALXPRT PETRO TAPE	3
812481	SEALXPRT UNDERWATER PETRO PASTE	3
812485	SEALXPRT PETRO TAPE	3
812486	SEALXPRT PETRO TAPE	3
812487	SEALXPRT PETRO TAPE	3
812488	SEALXPRT PETRO TAPE	3
812489	SEALXPRT PETRO TAPE	3
812491	SEALXPRT ULTRA SEALING TAPE	1
812492	SEALXPRT ULTRA SEALING TAPE	1
812493	SEALXPRT ULTRA SEALING TAPE	1
812591	SEALXPRT PS106 UNDERWATER EPOXY PUTTY	5
812593	SEALXPRT WR204 WEAR RESISTANT COATING	6
812594	SEALXPRT WR211 CORROSION RESISTANT COATING	6
812601	SEALXPRT RV527C CLEAR RTV SILICONE	11
812602	SEALXPRT RV527C CLEAR RTV SILICONE	11
812604	SEALXPRT RV527W WHITE RTV SILICONE	11
812605	SEALXPRT RV527W WHITE RTV SILICONE	11
812611	SEALXPRT FLANGE SEALANT FS518	8
812612	SEALXPRT FLANGE SEALANT FS510	8
812613	SEALXPRT FLANGE SEALANT FS510	8
812614	SEALXPRT FLANGE SEALANT FS510	8
812621	SEALXPRT FLANGE SEALANT FS515	8
812622	SEALXPRT FLANGE SEALANT FS515	8
812623	SEALXPRT FLANGE SEALANT FS515	8
812624	SEALXPRT FLANGE SEALANT FS515	8
812625	SEALXPRT FLANGE SEALANT FS515	8
812626	SEALXPRT FLANGE SEALANT FS515	8
812627	SEALXPRT FLANGE SEALANT FS518	8
812628	SEALXPRT FLANGE SEALANT FS518	8
812629	SEALXPRT FLANGE SEALANT FS518	8
812630	SEALXPRT FLANGE SEALANT FS518	8
812631	SEALXPRT FLANGE SEALANT FS515	8
812632	SEALXPRT FLANGE SEALANT FS518	8
812635	SEALXPRT FLANGE SEALANT FS510	8
812636	SEALXPRT FLANGE SEALANT FS510	8
812651	SEALXPRT FLANGE SEALANT FS518	8
812652	SEALXPRT THREAD SEALANT TS577	8
812656	SEALXPRT FLANGE SEALANT FS515	8
812657	SEALXPRT FLANGE SEALANT FS515	8

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
812661	SEALXPRT PL105 RUBBER REPAIR PUTTY	5
812662	SEALXPRT PL104 RUBBER REPAIR LIQUID	5
812671	SEALXPRT RV599A GREY RTV SILICONE	11
812672	SEALXPRT RV599 GREY RTV SILICONE	11
812691	SEALXPRT RV598 BLACK RTV SILICONE	11
812692	SEALXPRT RV527W WHITE RTV SILICONE	11
812693	SEALXPRT RV598 BLACK RTV SILICONE	11
812694	SEALXPRT RV527W WHITE RTV SILICONE	11
812695	SEALXPRT RV596 RED RTV SILICONE	11
812721	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812722	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812723	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812724	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812725	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812726	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812727	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812728	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812729	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812730	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812741	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812742	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812743	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812744	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812745	SEALXPRT THREADLOCKER AT243	7
812746	SEALXPRT THREADLOCKER AT270	7
812747	SEALXPRT FLANGE SEALANT FS515	8
812748	SEALXPRT THREAD SEALANT TS542	8
812749	SEALXPRT THREAD SEALANT TS577	8
812750	SEALXPRT RETAINING COMPOUND RC648	9
812751	SEALXPRT THREADLOCKER AT222	7
812752	SEALXPRT THREADLOCKER AT242	7
812753	SEALXPRT THREADLOCKER AT262	7
812754	SEALXPRT THREADLOCKER AT271	7
812755	SEALXPRT THREADLOCKER AT277	7
812756	SEALXPRT THREADLOCKER AT290	7
812758	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812759	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812760	SEALXPRT FLANGE SEALANT FS510	8
812761	SEALXPRT FLANGE SEALANT FS510	8
812762	SEALXPRT THREAD SEALANT TS542	8
812763	SEALXPRT RETAINING COMPOUND RC603	9
812764	SEALXPRT THREADLOCKER AT270	7
812765	SEALXPRT THREADLOCKER AT222	7
812766	SEALXPRT THREADLOCKER AT242	7
812767	SEALXPRT THREADLOCKER AT270	7
812768	SEALXPRT THREADLOCKER AT277	7
812769	SEALXPRT THREAD SEALANT TS542	8
812770	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812771	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812772	SEALXPRT CYANOACRYLATE ADHESIVE CA496	9
812773	SEALXPRT FLANGE SEALANT FS510	8
812774	SEALXPRT FLANGE SEALANT FS515	8
812775	SEALXPRT THREAD SEALANT TS545	8
812776	SEALXPRT THREAD SEALANT TS545	8
812777	SEALXPRT RETAINING COMPOUND RC638	9
812778	SEALXPRT ADHESIVE PRIMER	4
812781	SEALXPRT THREADLOCKER AT222	7
812782	SEALXPRT THREADLOCKER AT243	7

IMPA	SEALXPRT PRODUCTS EQUIVALENT	PAGE
812783	SEALXPRT THREADLOCKER AT262	7
812784	SEALXPRT THREADLOCKER AT271	7
812785	SEALXPRT THREADLOCKER AT277	7
812786	SEALXPRT THREADLOCKER AT290	7
812787	SEALXPRT CYANOACRYLATE ADHESIVE CA401	9
812788	SEALXPRT CYANOACRYLATE ADHESIVE CA401	9
812789	SEALXPRT CYANOACRYLATE ADHESIVE CA480	9
812790	SEALXPRT FLANGE SEALANT FS515	8
812791	SEALXPRT FLANGE SEALANT FS515	8
812792	SEALXPRT RV599A GREY RTV SILICONE	11
812793	SEALXPRT RV599 GREY RTV SILICONE	11
812794	SEALXPRT THREAD SEALANT TS542	8
812795	SEALXPRT THREAD SEALANT TS577	8
812796	SEALXPRT RETAINING COMPOUND RC603	9
812797	SEALXPRT RETAINING COMPOUND RC603	9
812798	SEALXPRT RETAINING COMPOUND RC648	9
812813	SEALXPRT FLANGE SEALANT FS518	8
812814	SEALXPRT FLANGE SEALANT FS518	8
812815	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812816	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812817	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812818	SEALXPRT CYANOACRYLATE ADHESIVE CA480	9
812819	SEALXPRT FLANGE SEALANT FS518	8
812820	SEALXPRT FLANGE SEALANT FS518	8
812821	SEALXPRT THREAD SEALANT TS545	8
812822	SEALXPRT THREAD SEALANT TS545	8
812823	SEALXPRT THREAD SEALANT TS567	8
812824	SEALXPRT THREAD SEALANT TS567	8
812825	SEALXPRT THREAD SEALANT TS567	8
812826	SEALXPRT RETAINING COMPOUND RC620	9
812827	SEALXPRT RETAINING COMPOUND RC620	9
812828	SEALXPRT RETAINING COMPOUND RC620	9
812829	SEALXPRT RETAINING COMPOUND RC638	9
812831	SEALXPRT RETAINING COMPOUND RC680	9
812832	SEALXPRT RETAINING COMPOUND RC680	9
812834	SEALXPRT FLANGE SEALANT FS518	8
812835	SEALXPRT FLANGE SEALANT FS515	8
812837	SEALXPRT RV587A BLUE RTV SILICONE	11
812838	SEALXPRT RV587 BLUE RTV SILICONE	11
812839	SEALXPRT RV587 BLUE RTV SILICONE	11
812840	SEALXPRT CYANOACRYLATE ADHESIVE CA495	9
812841	SEALXPRT RV598A BLACK RTV SILICONE	11
812842	SEALXPRT RV598 BLACK RTV SILICONE	11
812843	SEALXPRT RV598 BLACK RTV SILICONE	11
812844	SEALXPRT THREADLOCKER AT243	7
812845	SEALXPRT THREADLOCKER AT243	7
812846	SEALXPRT THREADLOCKER AT262	7
812847	SEALXPRT THREADLOCKER AT262	7
812848	SEALXPRT TS55 THREAD SEALING STRING	8
812849	SEALXPRT TS55 THREAD SEALING STRING	8
812901	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812902	SEALXPRT PS102 STEEL EPOXY PUTTY	5
812903	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812904	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812905	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812906	SEALXPRT PL103 ALUMINUM REPAIR LIQUID	5
812910	SEALXPRT PS104 BRONZE EPOXY PUTTY	5
812911	SEALXPRT PS104 BRONZE EPOXY PUTTY	5

IMPA	SEALXPert PRODUCTS EQUIVALENT	PAGE	IMPA	SEALXPert PRODUCTS EQUIVALENT	PAGE
812912	SEALXPert THREADLOCKER AT243	7	812976	SEAL STIC SS104 BRONZE EPOXY STICK	4
812913	SEALXPert THREADLOCKER AT243	7	812977	SEAL STIC SS102 STEEL EPOXY STICK	4
812914	SEALXPert THREADLOCKER AT243	7	812978	SEAL STIC SS102 STEEL EPOXY STICK	4
812915	SEALXPert THREADLOCKER AT270	7	812985	WRAP SEAL PLUS STANDARD RESIN AND ACTIVATOR	2
812916	SEALXPert THREADLOCKER AT270	7	815201	SEALXPert THREADLOCKER AT222	7
812917	SEALXPert THREADLOCKER AT270	7	815202	SEALXPert THREADLOCKER AT222	7
812918	SEALXPert THREADLOCKER AT242	7	815203	SEALXPert THREADLOCKER AT222	7
812919	SEALXPert THREADLOCKER AT242	7	815204	SEALXPert THREADLOCKER AT262	7
812920	SEALXPert THREADLOCKER AT242	7	815205	SEALXPert THREADLOCKER AT262	7
812921	SEALXPert PS103 ALUMINIUM EPOXY PUTTY	5	815206	SEALXPert THREADLOCKER AT262	7
812922	SEALXPert PS103 ALUMINIUM EPOXY PUTTY	5	815207	SEALXPert THREADLOCKER AT290	7
812923	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815208	SEALXPert THREADLOCKER AT290	7
812924	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815209	SEALXPert THREADLOCKER AT290	7
812925	SEAL STIC SS102 STEEL EPOXY STICK	4	815210	SEALXPert THREADLOCKER AT271	7
812926	SEAL STIC SS102 STEEL EPOXY STICK	4	815211	SEALXPert THREADLOCKER AT271	7
812927	SEALXPert CYANOACRYLATE ADHESIVE CA496	9	815212	SEALXPert FLANGE SEALANT FS515	8
812928	SEALXPert CYANOACRYLATE ADHESIVE CA496	9	815213	SEALXPert FLANGE SEALANT FS515	8
812929	SEALXPert CYANOACRYLATE ADHESIVE CA496	9	815214	SEALXPert THREAD SEALANT TS577	8
812931	SEALXPert PS107 5 MINUTES EPOXY PUTTY	5	815215	SEALXPert THREAD SEALANT TS577	8
812932	SEALXPert PS107 5 MINUTES EPOXY PUTTY	5	815216	SEALXPert RETAINING COMPOUND RC603	9
812933	SEALXPert PS103 ALUMINIUM EPOXY PUTTY	5	815217	SEALXPert RETAINING COMPOUND RC603	9
812934	SEALXPert PS103 ALUMINIUM EPOXY PUTTY	5	815218	SEALXPert RETAINING COMPOUND RC603	9
812935	SEALXPert PS106 UNDERWATER EPOXY PUTTY	5	815219	SEALXPert RETAINING COMPOUND RC638	9
812936	SEALXPert PS106 UNDERWATER EPOXY PUTTY	5	815220	SEALXPert RETAINING COMPOUND RC638	9
812937	SEALXPert WR211 CORROSION RESISTANT COATING	6	815221	SEALXPert RETAINING COMPOUND RC638	9
812938	SEALXPert WR211 CORROSION RESISTANT COATING	6	815222	SEALXPert RETAINING COMPOUND RC638	9
812939	SEALXPert WR211 CORROSION RESISTANT COATING	6	815223	SEALXPert RETAINING COMPOUND RC638	9
812940	SEALXPert WR211 CORROSION RESISTANT COATING	6	815224	SEALXPert RETAINING COMPOUND RC638	9
812941	SEALXPert WR204 WEAR RESISTANT COATING	6	815225	SEALXPert RETAINING COMPOUND RC648	9
812942	SEALXPert WR204 WEAR RESISTANT COATING	6	815226	SEALXPert RETAINING COMPOUND RC648	9
812943	SEALXPert PS105 STAINLESS STEEL EPOXY PUTTY	5	815227	SEALXPert RETAINING COMPOUND RC648	9
812944	SEALXPert PS105 STAINLESS STEEL EPOXY PUTTY	5	815231	SEALXPert FLANGE SEALANT FS515	8
812945	SEALXPert PS110 TITANIUM EPOXY PUTTY	5	815232	SEALXPert FLANGE SEALANT FS515	8
812946	SEALXPert PS110 TITANIUM EPOXY PUTTY	5	815233	SEALXPert FLANGE SEALANT FS515	8
812947	SEALXPert PL103 ALUMINUM REPAIR LIQUID	5	815240	SEALXPert CYANOACRYLATE ADHESIVE CA495	9
812948	SEALXPert PL103 ALUMINUM REPAIR LIQUID	5	815241	SEALXPert CYANOACRYLATE ADHESIVE CA495	9
812949	SEALXPert WR204 WEAR RESISTANT COATING	6	815245	SEALXPert CYANOACRYLATE ADHESIVE CA401	9
812950	SEALXPert WR204 WEAR RESISTANT COATING	6	815246	SEALXPert CYANOACRYLATE ADHESIVE CA401	9
812951	SEALXPert PS102 STEEL EPOXY PUTTY	5	815247	SEALXPert CYANOACRYLATE ADHESIVE CA401	9
812952	SEALXPert PS108 HI-TEMP EPOXY PUTTY	5	815248	SEALXPert CYANOACRYLATE ADHESIVE CA401	9
812953	SEALXPert PS108 HI-TEMP EPOXY PUTTY	5	815253	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812954	SEALXPert PS108 HI-TEMP EPOXY PUTTY	5	815254	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812965	SEAL STIC SS103 ALUMINUM EPOXY STICK	4	815255	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812966	SEAL STIC SS103 ALUMINUM EPOXY STICK	4	815256	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812967	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815257	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812968	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815258	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812969	SEAL STIC SS102 STEEL EPOXY STICK	4	815259	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812970	SEAL STIC SS102 STEEL EPOXY STICK	4	815260	SEALXPert CYANOACRYLATE ADHESIVE CA480	9
812971	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815282	SEALXPert RV596A RED RTV SILICONE	11
812972	SEAL STIC SS106 UNDERWATER EPOXY STICK	4	815283	SEALXPert RV596 RED RTV SILICONE	11
812973	SEAL STIC SS102 STEEL EPOXY STICK	4	815284	SEALXPert RV598A BLACK RTV SILICONE	11
812974	SEAL STIC SS102 STEEL EPOXY STICK	4	815285	SEALXPert RV598 BLACK RTV SILICONE	11
812975	SEAL STIC SS104 BRONZE EPOXY STICK	4	815286	SEALXPert RV598 BLACK RTV SILICONE	11

SealXpert® Products offer a range of proven maintenance and repair products that are unique in pipeline service. These products eliminate or minimize the cost of plants and equipment downtime.

Our range of maintenance and repair products are used for leak repair, corrosion protection and reinforcement, parts repair and rebuilding, corrosion and wear coating, pipeline rehabilitation, etc. Each of the products are engineered to be applied on many applications.



Wrap Seal® Quick Repair Kit for Pipe Leaks (Water Activated Tape)

PRODUCT NAME	IMPA CODE
Wrap Seal WS0205 - Quick Repair Kit for Pipe Leaks 2" x 5' (50 mm x 1.5 m)	812361 / 812451
Wrap Seal WS0206 - Quick Repair Kit for Pipe Leaks 2" x 6' (50 mm x 1.8 m)	812364 / 812173
Wrap Seal WS0212 - Quick Repair Kit for Pipe Leaks 2" x 12' (50 mm x 3.6 m)	812362 / 812174
Wrap Seal WS0309 - Quick Repair Kit for Pipe Leaks 3" x 9' (75 mm x 1.5 m)	812365 / 812452
Wrap Seal WS0412 - Quick Repair Kit for Pipe Leaks 4" x 12' (100 mm x 3.6 m)	812363 / 812453
Wrap Seal PLUS Fiberglass Repair Tape 4" x 20' (100 mm x 6.0 m)	812454
Wrap Seal PLUS Fiberglass Repair Tape 4" x 30' (100 mm x 9.1 m)	812455
Wrap Seal PLUS Fiberglass Repair Tape 6" x 20' (150 mm x 6.0 m)	812457
Wrap Seal PLUS Fiberglass Repair Tape 6" x 30' (150 mm x 9.1 m)	812458

Features:

- Repairs leak in 30 minutes
- Applicable to pipes up to 18" (457 mm) diameter
- Applicable on any metal or non-metal pipes
- Repairs T-joint, elbow joint, valve thread, valve body
- Withstand pressure up to 400 psi (28 kg/cm²)
- Withstand temperature up to 200 °C (392 °F)
- Safe for drinking water and resistant to most chemicals
- Reinforce and strengthen pipe after repair
- Permanent repair and extend service life of pipes

Technical data:

Pressure tested	:	1/2" (15 mm) steel pipe with 1/8" (3 mm) hole when repaired with Wrap Seal® withstands 4,000 psi (281 kg/cm ²)
	:	1/2" (15 mm) steel pipe with 1/2" (13 mm) hole when repaired with Wrap Seal® withstands 600 psi (42 kg/cm ²)
Tensile strength	:	3,920 psi (276 kg/cm ²)
Bond strength	:	230 psi (16 kg/cm ²)
Tensile elongation	:	1.2 % ± 0.7 %
Compression strength	:	13,750 ± 530 psi (967 ± 37 kg/cm ²)
Yield strength	:	2,260 psi (159 kg/cm ²)
Cured hardness	:	82 Shore D



SealXpert® Pipe Tapes and Pipe Repair Kit

PRODUCT NAME	IMPA CODE
SealXpert Pipe Tapes (5 rolls 2" x 6' water-activated tape)	812344
SealXpert Pipe Tapes (4 rolls 2" x 12' water-activated tape)	812348
SealXpert Pipe Repair Kit (5 rolls 2" x 6' water-activated tape + Seal Stic)	812367

Features:

- Repairs under active leaks
- Repairs leak in 30 minutes
- Withstand pressure up to 400 psi (28 kg/cm²)
- Withstand temperature up to 200 °C (392 °F)
- Safe for drinking water and resistant to most chemicals
- Ideal for pipeline reinforcement

Technical data:

Tensile strength	:	3,916 psi (275 kg/cm ²)
Bond strength	:	232 psi (16 kg/cm ²)
Compressive strength	:	13,634 psi (959 kg/cm ²)
Yield strength	:	4,061 psi (286 kg/cm ²)
Tensile elongation	:	2,611 psi (184 kg/cm ²)
Hardness	:	93 Shore D
Temperature range	:	-29 °C – 200 °C (-20 °F – 392 °F)



SealXpert® Ultra Sealing Tape

PRODUCT NAME	IMPA CODE
SealXpert Ultra Sealing Tape 1" x 16' (25 mm x 5 m)	812175
SealXpert Ultra Sealing Tape 1" x 33' (25 mm X 10 m)	812491
SealXpert Ultra Sealing Tape 1½" x 33' (38 mm X 10 m)	812492
SealXpert Ultra Sealing Tape 2" x 33' (50 mm X 10 m)	812493

Features:

- Seals active pipe leaks up to 150 psi (11 kg/cm²)
- High tensile and dielectric strength
- Superior bonding properties
- Bond to itself, no adhesive required
- Excellent air and moisture control
- Seals irregular shapes
- Flame-retardant
- Resists weathering

Technical data:

Thickness	:	0.02" (0.5 mm)
Cold brittle point	:	-50 °C (-58 °F)
Tensile strength	:	700 psi (49 kg/cm ²)
Elongation, Min.	:	300%
Specific gravity	:	1.17
Volume resistivity	:	1 × 10 ¹³ Ω/cm
Water absorption	:	3% by weight
Dielectric strength	:	400 Volts/mil
Hardness	:	50 Shore A
Break strength	:	40 lbs (18 kg)



Wrap Clamp™ WC1 Leak Repair Clamps

PRODUCT NAME	IMPA CODE
Wrap Clamp WC1 DN50 x 80mm	614170 / 614180
Wrap Clamp WC1 DN65 x 140mm	614171 / 614181
Wrap Clamp WC1 DN80 x 200mm	614172 / 614182
Wrap Clamp WC1 DN100 x 200mm	614173 / 614183
Wrap Clamp WC1 DN125 x 200mm	614174 / 614184
Wrap Clamp WC1 DN150 x 200mm	614175 / 614185
Wrap Clamp WC1 DN200 x 255mm	614176 / 614186
Wrap Clamp WC1 DN250 x 255mm	614177 / 614187
Wrap Clamp WC1 DN300 x 255mm	614178 / 614188

Features:

- Single side locking clamp
- Easy to handle, quick and simple to install
- No special tools or expertise required
- Stainless steel 304 / 316 material


Sizes and technical data:

Model	O.D.		O.D. Range	Length, L	Max Expansion Distance	MAX Pipe Distance (for Connection), G	Pressure	Weight
	Inch	mm						
WC1-50A80	2	60.5	59-61	80	40	20 ± 15	363 (26)	0.8
WC1-65A140	2 ½	76.3	75-78	140	100	20 ± 15	363 (26)	1.5
WC1-80A200	3	89.1	88-91	203	150	25 ± 20	232 (16)	3.1
WC1-100A200	4	114	106-117	203	150	25 ± 20	232 (16)	3.4
WC1-125A200	5	140	138-142	204	150	30 ± 25	232 (16)	4.7
WC1-150A200	6	168	158-170	204	150	30 ± 25	232 (16)	5.9
WC1-200A255	8	219	216-222	255	150	30 ± 25	174 (12)	12.2
WC1-250A255	10	273	272-276	255	150	30 ± 25	174 (12)	13.5
WC1-300A255	12	325	324-328	255	150	30 ± 25	145 (10)	16.3

SealXpert® Repair Patch

PRODUCT NAME	IMPA CODE
SealXpert Repair Patch (8cm x 12cm)	812298

Features:

- Easy to use, fast installation
- Hardens to a tough, durable waterproof finish in minutes
- Excellent adhesion to iron, steel, stainless steel, titanium, fiberglass, aluminum, wood, ceramics, composites, acrylics, PVC, and most other plastics

Technical data:

Tensile Strength	: 10,000 psi (703 kg/cm²)
Tensile Modulus	: 192,000 psi (13,499 kg/cm²)
Tensile Elongation	: 15-25%
Dielectric Strength	: 250 volts/mils
Flexural strength	: 19,000 psi (1,336 kg/cm²)
Hardness	: 70 Shore D



CORROSION REPAIR AND REINFORCEMENT

Wrap Seal PLUS® Resin and Activator

PRODUCT NAME	IMPA CODE
Wrap Seal PLUS Standard Resin and Activator (500 grams)	812301 / 812302 / 812234 / 812985 / 812216 / 812209 / 812741 / 812742 / 812743 / 812744

Features:

- Corrosion barrier and isolator
- High adhesion strength
- Excellent alkali and acid resistance
- Ease of application by using paint rollers and paint brush
- Applicable for pipes, tanks, and large surfaces

Technical data:

Viscosity	: 20,000 – 40,000 cps at 21 °C (70 °F)
Specific gravity	: 1.85
Compressive strength	: 24,500 psi (1,723 kg/cm²)
Tensile strength	: 35,000 psi (2,461 kg/cm²)
Bond strength	: 500 psi (35 kg/cm²)
Flexural strength	: 42,000 psi (2,953 kg/cm²)
Flexural modulus	: 1.6x10 ⁶ psi (112,491 kg/cm²)
Barcol hardness	: 40 - 50 Shore D
Coverage area (per set)	: 0.15 m² at 3 mm thickness



CORROSION REPAIR AND REINFORCEMENT

Wrap Seal PLUS® Glass Tape and Glass Cloth

PRODUCT NAME	IMPA CODE
Wrap Seal PLUS Glass Tape 2" x 164' (50 mm x 50 m)	811712 / 812223 / 812339 / 812222 / 812323 / 812324 / 811710 / 811711 / 811713 / 812224
Wrap Seal PLUS Glass Tape 4" x 164' (100 mm x 50 m)	811715 / 812225 / 812325 / 811714
Wrap Seal PLUS Glass Cloth 1 m x 1 m	812321 / 812322 / 811703 / 811701 / 811702

Features:

- Made by weaving yarn into cloth on a loom state
- Specially designed for use in filament winding applications with epoxy resin systems
- Suitable for the manufacturer of length-limitless pole, tube, tanks, pipes and structural products with high strength and high fiber content
- Not hazardous

Technical data:

Glass type	: E-Glass
Weight	: 156 gm/m ²
Thickness	: 0.15 mm / 0.50 mm
Weft	: 14 yarns/inch
Warp	: 17 yarns/inch
Weaving pattern	: Plain
Tensile strength	: Warp – 520 N/cm Weft – 430 N/cm
Softening point	: 840 °C (1,544 °F)
Max. moisture absorption rate	: 0.3%



CORROSION PROTECTION

SealXpert® Underwater Petro Paste

PRODUCT NAME	IMPA CODE
SealXpert Underwater Petro Paste	812481

Features:

- Petrolatum based compound
- Contains no Volatile Organic Compounds
- Can be applied by inexperienced personnel
- No shut downs or cure time is necessary
- Can be applied to very wet or underwater surfaces

Technical data:

Solid content	: 100 %
Flash point	: > 180 °C (> 356 °F)
Specific gravity	: 1.08
Specific volume	: 925 cc/kg
Coverage	: 2-5mm ² /kg
Temperature range	:
For application	: 5 °C (41 °F)
For service	: -25 °C to 50 °C (-13 °F to 122 °F)



SealXpert® Petro Tape

PRODUCT NAME	IMPA CODE
SealXpert Petro Tape 2" x 33' (50 mm x 10 m)	812471
SealXpert Petro Tape 4" x 33' (100 mm x 10 m)	812472 / 812485 / 812487 / 812489
SealXpert Petro Tape 6" x 33' (150 mm x 10 m)	812473 / 812486 / 812488
SealXpert Petro Tape 8" x 33' (200 mm x 10 m)	812474 / 812475

Features:

- Non-hardening, non-cracking
- Highly resistant to mineral acids, alkalis, salts and micro-organisms
- Highly impermeable to water, water vapour and gases
- Used for the protection of buried or exposed pipes, rods, cables, valves and metal fittings from corrosion

Technical data:

Dielectric strength	: 250 Volts/mil
Thickness	: 1,100 Micron
Breaking strength	: 7,200 n/m
Elongation at break	: 20 %
Flash point	: > 40 °C (104 °F)
Water vapour transmission	: < 1.0 Ng/Pa.S.m ²
Petrolatum components	: 60%
Drop melting points	: 84 °C (183 °F)
Cone penetration	: 6.3 nm




CORROSION PROTECTION

SealXpert® Hatch Cover Tape and Strips

PRODUCT NAME	IMPA CODE
SealXpert Hatch Cover Tape (75 mm x 20 m x 2 mm x 4 rolls)	232441 / 232451 / 232458 / 232464
SealXpert Hatch Cover Tape (100 mm x 20 m x 2 mm x 3 rolls)	232448 / 232442 / 232445 / 232456 / 232459 / 232465 / 232454 / 232452
SealXpert Hatch Cover Tape (150 mm x 20 m x 2 mm x 2 rolls)	232449 / 232443 / 232446 / 232453 / 232457 / 232460 / 232466 / 232455
SealXpert Hatch Cover Strips (100 mm x 1.22 m x 4 mm x 30 strips)	232462 / 232472 / 232468 / 232475 / 232478 / 232470 / 232461 / 232467 / 232474 / 232477
SealXpert Hatch Cover Strips (150 mm x 1.22 m x 4 mm x 30 strips)	232463 / 232473 / 232469 / 232476 / 232479 / 232480 / 430311

Features:

- Excellent asphalt based adhesive
- Easy to apply
- No remains on removal
- No preheating required
- Good adhesion on hot and cold weather
- Designed for hatch joint water-tightening



REPAIR AND REBUILDING

Seal Stic® Quick Cure Epoxy Sticks

PRODUCT NAME	IMPA CODE
Seal Stic SS102 Quick Cure Steel Epoxy Stick (115 grams)	812342 / 812190 / 812191 / 812202 / 812925 / 812926 / 812973 / 812974 / 812308 / 812220 / 812969 / 812970 / 812977 / 812978
Seal Stic SS103 Quick Cure Aluminum Epoxy Stick (115 grams)	812965 / 812966
Seal Stic SS104 Quick Cure Bronze Epoxy Stick (115 grams)	812975 / 812976 / 812204
Seal Stic SS106 Quick Cure Underwater Epoxy Stick (115 grams)	812193 / 812293 / 812294 / 812343 / 812923 / 812924 / 812375 / 812207 / 812967 / 812968 / 812971 / 812972

Features:

- High performance hand-mouldable metal-filled epoxies with industrial strength
- Used to fill and repair holes, cracks and defects
- Quick-curing
- Cost-effective in returning worn-off parts or equipment back to service
- No special tools or hot work required
- Safe for drinking water and resistant to most chemicals
- Can be machined, drill and tap, filled or painted after cured

Technical data:

Compressive strength	: 12,000 psi (844 kg/cm ²)
Tensile strength	: 6,000 psi (422 kg/cm ²)
Shear strength	: 900 psi (63 kg/cm ²)
Hardness	: 80 Shore D
Temperature range	: -50 °C to 120 °C (-58 °F to 248 °F)
Pot life (100g mixture)	: 10 min
Min. curing time before function	: 20 min



SealXpert® Adhesive Primer

PRODUCT NAME	IMPA CODE
SealXpert Adhesive Primer (150 ml)	812778

Features:

- Excellent adhesion to the pipe substrate
- Excellent cathodic disbondment resistance
- Non-toxic
- Non-polluting
- Conform to local and national standards

Technical data:

Colour	: Black
Base	: Rubber and synthetic resins
Solvent	: V.E. & P Naphtha
Total solids	: 30%
Viscosity	: Medium syrup
Flash point	: 10°C (50°F)
Maximum operating temperature	: 85°C (185°F)

REPAIR AND REBUILDING

SealXpert® Repair Liquid and Putty

PRODUCT NAME	IMPA CODE
SealXpert PL102 Steel Repair Liquid (500 grams)	812179 / 812180 / 812256 / 812357 / 812391 / 812392 / 812201 / 812257
SealXpert PL103 Aluminium Repair Liquid (500 grams)	812176 / 812271 / 812272 / 812905 / 812906 / 812947 / 812948 / 812903 / 812904
SealXpert PL104 Rubber Repair Liquid (500 grams)	812249 / 812393 / 812394 / 812662
SealXpert PL105 Rubber Repair Putty (350 grams)	812187 / 812188 / 812248 / 812385 / 812386 / 812387 / 812661

Features:

- Aluminium Repair Liquid
 - ✓ Aluminium filled pourable epoxy for making molds, patterns, and holding fixtures that can be machined, drilled, or tapped
- Steel Repair Liquid
 - ✓ Steel filled, liquid epoxy designed for maintaining and/or repairing tooling, mold making, and leveling equipment
- Rubber Repair Liquid
 - ✓ High initial bonding strength, good toughness, curing at room temperature
 - ✓ Designed to bond joints of fabric, reinforce multilayer rubber conveyor belt in metallurgy, power, coal mining, etc. industries
- Rubber Repair Putty
 - ✓ Fast curing at room temperature, non-toxic after cured, good flexibility, high tensile strength, high tearing strength, good abrasion, corrosion, aging and impact resistance



Technical data:

Aluminium Repair Liquid

Pot Life(100G@25°C)	: 75 min
Dielectric Strength	: 4 KV/mm
Adhesive Tensile Shear	: 2,698 psi (190 kg/cm ²)
Compressive Strength	: 9,863 psi (694 kg/cm ²)
Hardness	: 85 Shore D

Steel Repair Liquid

Adhesive Tensile Shear	: 2,800 psi (197 kg/cm ²)
Tensile Strength	: 3,220 psi (227 kg/cm ²)
Compressive Strength	: 10,196 psi (717 kg/cm ²)
Modulus of Elasticity	: 274,992 psi (19,334 kg/cm ²)
Dielectric Strength	: 1,181 volts/mm
Flexural Strength	: 5,599 psi (394 kg/cm ²)
Hardness	: 85 Shore D

Rubber Repair Liquid

Pot Life(100G@25°C)	: 80 min
Peeling Strength	: 2 Hour - 25 N/cm
	: 24 Hour - 45 N/cm
Max. Working Temperature	: 80 °C (176 °F)

Rubber Repair Putty

Pot Life(100G@25°C)	: 7 min
Peeling Strength	: 95 N/m
Tensile Strength	: 2,901 psi (204 kg/cm ²)
Tearing Strength	: 70 N/cm
Elongation	: 400 %
Hardness	: 75 Shore A

SealXpert® Metal Repair Putties

PRODUCT NAME	IMPA CODE
SealXpert PS102 Steel Epoxy Putty (454 grams)	812181 / 812182 / 812211 / 812251 / 812252 / 812335 / 812356 / 812371 / 812372 / 812398 / 812399 / 812901 / 812902 / 812951 / 812253 / 812395 / 812306 / 812310
SealXpert PS103 Aluminium Epoxy Putty (454 grams)	812177 / 812266 / 812267 / 812358 / 812921 / 812922 / 812933 / 812934
SealXpert PS104 Bronze Epoxy Putty (227 grams)	812290 / 812910 / 812911 / 812203 / 812212
SealXpert PS105 Stainless Steel Epoxy Putty (454 grams)	812178 / 812292 / 812359 / 812943 / 812944
SealXpert PS106 Underwater Epoxy Putty (454 grams)	812246 / 812195 / 812315 / 812334 / 812336 / 812591 / 812935 / 812936
SealXpert PS107 5 minutes Epoxy Putty (454 grams)	812199 / 812262 / 812347 / 812355 / 812397 / 812931 / 812932 / 812197 / 812247 / 812198
SealXpert PS108 Hi-Temp Epoxy Putty (454 grams)	812345 / 812346 / 812952 / 812953 / 812954 / 812239 / 812240 / 812245 / 812340 / 812238
SealXpert PS109 Supermetal Epoxy Putty (454 grams)	812185 / 812186 / 812243 / 812351 / 812352 / 812353 / 812396
SealXpert PS110 Titanium Epoxy Putty (454 grams)	812241 / 812242 / 812945 / 812946

Features:

- High performance metal-filled epoxies
- The best choice for repairing holes, cracks and defects
- Quick-curing and cost-effective in returning worn-off parts or equipment back to service
- Can be drilled, tapped, machined or painted



SealXpert® Metal Repair Putties

Product No. / Colour	Compressive Strength psi (kg/cm ²)	Tensile Strength psi (kg/cm ²)	Shear Strength psi (kg/cm ²)	Hardness Shore D	Temperature Range °C (°F)	Mixture (A:B)		Pot Life min	Curing Time		Coverage Area (per set) cm ² at 0.2" (6 mm) thickness
						Weight	Volume		50% load (hour)	100% load (hour)	
PS 102 Steel Epoxy Putty Colour: Grey	18,130 (1,275)	4,931 (347)	2,901 (204)	80	-50 to 160 (-58 to 320)	9:1	5:1	40	8	24	450
PS 103 Aluminium Epoxy Putty Colour: Aluminium	14,214 (999)	4,351 (306)	2,611 (184)	80	-50 to 160 (-58 to 320)	6:1	3.5:1	50	12	24	503
PS 104 Bronze Epoxy Putty Colour: Bronze	13,779 (969)	4,351 (306)	2,611 (184)	80	-50 to 170 (-58 to 338)	9:1	3:1	40	12	24	165
PS 105 Stainless Steel Epoxy Putty Colour: Dark Grey	15,229 (1,071)	4,931 (347)	2,901 (204)	80	-50 to 160 (-58 to 320)	11:1	3.75:1	50	12	24	465
PS 106 Underwater Epoxy Putty Colour: Brown	13,053 (918)	4,496 (316)	2,611 (184)	80	-50 to 150 (-58 to 302)	5:1	3.5:1	20	6	12	472
PS 107 5 minutes Epoxy Putty Colour: Dark Grey	13,053 (918)	3,626 (255)	2,611 (184)	80	-50 to 120 (-58 to 248)	1.7:1	1:1	5	1/6	1	450
PS 108 Hi-Temp Epoxy Putty Colour: Dark Grey	12,908 (908)	4,351 (306)	2,611 (184)	80	-50 to 280 (-58 to 536)	5:1	4:1	60	6	12	432
PS 109 Superalloy Epoxy Putty Colour: Dark Grey	24,656 (1,733)	7,977 (561)	3,046 (214)	90	-50 to 160 (-58 to 320)	2:1	2:1	50	12	24	450
PS 110 Titanium Epoxy Putty Colour: Dark Grey	18,855 (1,326)	4,061 (286)	2,031 (143)	87	-50 to 160 (-58 to 320)	11:1	3.75:1	21	8	16	450

SealXpert® Wear and Corrosion Resistant Coating

PRODUCT NAME	IMPA CODE
SealXpert WR204 Wear Resistant Coating (500 grams)	812183 / 812184 / 812281 / 812377 / 812378 / 812593 / 812941 / 812942 / 812949 / 812950 / 251711 / 251712 / 251713 / 251705
SealXpert WR211 Corrosion Resistant Coating (500 grams)	812286 / 812337 / 812338 / 812594 / 812230 / 812231 / 812312 / 812381 / 812382 / 812388 / 812937 / 812938 / 812939 / 812940
SealXpert Common Marine Putty (5.0 Kg)	251471 / 251472 / 251473 / 251476 / 251477 / 251481 / 251482

Features:

- WR204
 - ✓ Ceramic microsphere and silicon alloy filled two-component epoxy coating
 - ✓ Suitable for application on vertical surfaces
 - ✓ Coating has strong adhesion and excellent properties of wear and impact resistance
- WR211
 - ✓ Composed of modified epoxy, wear resistant ceramic and crystal mineral powder
 - ✓ Thixotropic viscosity, suitable for application on vertical surface
 - ✓ Excellent resistance to strong alkali and acid



Product No. / Colour	Compressive Strength psi (kg/cm ²)	Tensile Strength psi (kg/cm ²)	Shear Strength psi (kg/cm ²)	Hardness Shore D	Temperature Range °C (°F)	Mixture (A:B)		Pot Life min	Curing Time		Coverage Area (per set) cm ² at 0.2" (6 mm) thickness
						Weight	Volume		50% load (hour)	100% load (hour)	
WR 204 Wear Resistant Coating Colour: Dark grey	15,954 (1,122)	4,351 (306)	2,176 (153)	90	-50 to 121 (-58 to 250)	4:1	4:1	40	10	24	378
WR 211 Corrosion Resistant Coating Colour: Dark grey	13,053 (918)	4,351 (306)	1,450 (102)	73	-50 to 121 (-58 to 250)	5:1	4:1	60	-	-	378

REPAIR AND REBUILDING

SealXpert® Epoxy Coating

PRODUCT NAME	IMPA CODE
SealXpert Anti-Slip Floor Coating (3.8 Litres)	251611 / 251612 / 251701 / 251702 / 251703 / 251704 / 251247 / 251231 / 251232 / 251233 / 251234 / 251235 / 251236 / 251241 / 251242 / 251243 / 251244 / 251245 / 251246
SealXpert Anti-Corrosive Epoxy Coating (10 Litres)	250822 / 250824 / 251012 / 251014 / 251034 / 251035 / 251043 / 251044 / 251054 / 251055 / 251061 / 251062 / 251074 / 251075 / 251096 / 251097 / 251084 / 251085 / 251621

Features:

- Two-component Epoxy Resin Coating designed for application in areas of heavy pedestrian traffic or light rolling traffic under typical dry service temperatures of -29°C to 60°C (-20°F to 140°F)
- Easy and fast to apply by paint brush or roller
- Reduces accidents (slips and falls) in the workplace
- Fire retardant in the cured state
- Resists gasoline, oil, acids, alkalis and aliphatic solvents
- Available in yellow, grey or green



SealXpert® Marine Chock

PRODUCT NAME	IMPA CODE
SealXpert MC38 Marine Chock (4 Litres)	251707 / 251710

Features:

- Two-part pourable chocking compound with excellent mechanical strength
- Allow pouring up to 80mm thickness
- High compressive strength and impact strength
- Excellent resistant to chemicals
- Applicable to mounting main engines, auxiliary gears, compressors, pumps, thrust and support bearings, etc.



MAINTENANCE

SealXpert® Anaerobic Threadlockers

PRODUCT NAME	IMPA CODE
SealXpert Threadlocker AT222, Low Strength (50 ml)	812751 / 812765 / 812781 / 815201 / 815202 / 815203
SealXpert Threadlocker AT242, Medium Strength (50 ml)	812752 / 812766 / 812918 / 812919 / 812920
SealXpert Threadlocker AT243, Medium Strength (50 ml)	812745 / 812844 / 812845 / 812912 / 812913 / 812914 / 812782
SealXpert Threadlocker AT262, High Strength (50 ml)	812753 / 812846 / 812847 / 815204 / 815205 / 815206 / 812783
SealXpert Threadlocker AT270, High Strength (50 ml)	812746 / 812764 / 812767 / 812915 / 812916 / 812917
SealXpert Threadlocker AT271, High Strength (50 ml)	812754 / 812784 / 815210 / 815211
SealXpert Threadlocker AT277, High Strength (50 ml)	812755 / 812768 / 812785
SealXpert Threadlocker AT290, Medium Strength (50 ml)	812756 / 812786 / 815207 / 815208 / 815209

Features:

- Designed to lock and seal threaded fasteners to prevent loosening and leakage
- Has excellent chemical and environmental resistance
- Available in a wide range of strength and viscosity for different applications



Product No.	Typical Use	Max Gap Fill mm	Uncured			Cured			Curing Speed	
			Colour	Viscosity mPa.s	Specific Gravity g/cm³	Breakaway Torque Nm	Prevail Torque Nm	Temperature Range °C (°F)	Fixture min	Full Cure hour
AT222	M2 – M8, removable	0.13	Purple	1,200 Thixotropic	1.05	6	4	-50 to 150 (-58 to 302)	10 - 20	24
AT242	M8-M16, removable	0.13	Blue	1,700 Thixotropic	1.05	12	5	-50 to 150 (-58 to 302)	10 - 20	24
AT243	M8-M20, slight oil contamination	0.13	Blue	2,250 Thixotropic	1.05	20	7	-50 to 150 (-58 to 302)	10 - 20	24
AT262	M10-M26, permanent locking and sealing	0.13	Red	1,800 Thixotropic	1.10	22	30	-50 to 150 (-58 to 302)	10 - 20	24
AT270	M25, permanent locking and sealing	0.13	Green	500	1.10	26	36	-50 to 150 (-58 to 302)	10 - 20	24
AT271	M16-M26, permanent locking and sealing	0.13	Red	500	1.12	27	30	-50 to 150 (-58 to 302)	10 - 20	24
AT277	M24-M36, permanent locking and sealing	0.25	Red	7,000	1.12	30	30	-50 to 150 (-58 to 302)	23 - 30	24
AT290	Under M12, wicking grade	0.10	Green	12	1.08	10	26	-50 to 150 (-58 to 302)	5 - 15	24

SealXpert® Anaerobic Thread Sealants and Thread Sealing String

PRODUCT NAME	IMPA CODE
SealXpert Thread Sealant TS542, fine threads (50 ml)	812748 / 812794 / 812762 / 812769
SealXpert Thread Sealant TS545, fine threads (50 ml)	812775 / 812776 / 812821 / 812822
SealXpert Thread Sealant TS567 (50 ml)	812823 / 812824 / 812825
SealXpert Thread Sealant TS577, coarse threads (50 ml)	812749 / 812795 / 815214 / 815215 / 812651 / 812652 / 812420 / 450419
SealXpert TS55 Thread Sealing String (150 m)	812848 / 812849

Features:

- Designed to seal and secure pipeline fittings for low and high pressure applications, filling the gap between threaded metal parts and stopping leakage and rust after cured



Product No.	Typical Use	Max Diameter of Thread mm	Uncured			Cured	
			Colour	Viscosity mPa.s	Specific Gravity g/cm ³	Max. Sealing pressure psi (kg/cm ²)	Temperature Range °C (°F)
TS542	Fine threads	M36	Brown	1,850 thixotropic	1.06	10,153 (714)	-50 to 150 (-58 to 302)
TS545	For hydraulic and pneumatic pipeline thread sealing	M36, tapered	Purple	14,000 thixotropic	1.05	10,080 (709)	-50 to 150 (-58 to 302)
TS567	General purpose, stainless steel pipe thread sealing	M80	White	550,000	1.15	10,298 (724)	-50 to 200 (-58 to 392)
TS577	Coarse thread sealing	M80, tapered/straight	Yellow	100,000 thixotropic	1.10	9,427 (663)	-50 to 150 (-58 to 302)
TS55	General purpose pipe threads	N.A.	white	N.A.	1.25	9,860 (693)	-50 to 150 (-58 to 302)

SealXpert® Anaerobic Flange Sealants

PRODUCT NAME	IMPA CODE
SealXpert Flange Sealant FS510 (50 ml)	812760 / 812761 / 812773 / 812612 / 812613 / 812614 / 812635 / 812636
SealXpert Flange Sealant FS515 Gasket Eliminator (50 ml)	812774 / 812790 / 812791 / 812656 / 812657 / 812835 / 815231 / 815232 / 815233 / 815212 / 815213 / 812747 / 812621 / 812622 / 812623 / 812624 / 812625 / 812626 / 812631
SealXpert Flange Sealant FS518 (50 ml)	812813 / 812814 / 812819 / 812820 / 812834 / 812611 / 812627 / 812628 / 812629 / 812630 / 812632

Features:

- Designed to fill small gaps
- Creates a rigid or flexible gasket between two mating flanges after cured
- It improves loading capability, reduces noises
- Has excellent solvent and chemical resistance
- Can be applied manually or via dispensers



Product No.	Typical Use	Max Gap Fill mm	Uncured			Cured		Curing Speed
			Colour	Viscosity mPa.s	Specific Gravity g/cm ³	Max. Seal Pressure Psi (kg/cm ²)	Temperature Range °C (°F)	Full Cure Hour
FS510	High temperature and solvent resistant	0.25	Pink	40,000 – 140,000	1.10	4,641 (326)	-55 to 200 (-67 to 392)	24
FS515	General purpose	0.25	Purple	1,200,000 Thixotropic	1.10	4,351 (306)	-50 to 150 (-58 to 302)	24
FS518	Aluminium	0.25	Red	900,000	1.10	4,351 (306)	-50 to 150 (-58 to 302)	24

SealXpert® Retaining Compounds

PRODUCT NAME	IMPA CODE
SealXpert Retaining Compound RC603 (50 ml)	812796 / 812797 / 815216 / 815217 / 815218 / 812763
SealXpert Retaining Compound RC620 (50 ml)	812826 / 812827 / 812828
SealXpert Retaining Compound RC638 (50 ml)	812777 / 812829 / 815222 / 815223 / 815224 / 815219 / 815220 / 815221
SealXpert Retaining Compound RC648 (50 ml)	812750 / 812798 / 815225 / 815226 / 815227
SealXpert Retaining Compound RC680 (50 ml)	812831 / 812832

Features:

- Designed to seal and secure non-threaded cylindrical shaft-shaft liner assemblies
- Are used to fill inner voids between two components and cure to form a strong precision assembly
- Can be applied manually or via a dispenser



Product No.	Typical Use	Max Gap Fill mm	Uncured			Cured		Curing Speed	
			Colour	Viscosity mPa.s	Specific Gravity g/cm³	Shear Strength Psi (kg/cm²)	Temperature Range °C (°F)	Fixture min	Full Cure hour
RC603	Slightly oil contaminated surface	0.13	Green	200	1.10	> 2,901 (> 204)	-50 to 150 (-58 to 302)	5 - 10	24
RC620	high temperatures 232 °C (450 °F)	0.30	Green	8,500	1.15	> 2,901 (> 204)	-50 to 230 (-58 to 446)	30 - 100	24
RC638	Maximum strength	0.26	Green	2,500	1.09	> 4,496 (> 316)	-50 to 150 (-58 to 302)	5 - 10	24
RC648	Withstands continuous working high temperature up to 175 °C (347 °F)	0.15	Green	500	1.25	> 2,611 (> 184)	-50 to 175 (-58 to 347)	5 - 15	24
RC680	For clearance and transition fit	0.25	Green	1,250	1.12	> 2,756 (> 194)	-50 to 150 (-58 to 302)	10 - 15	24

SealXpert® Cyanoacrylate Adhesive

PRODUCT NAME	IMPA CODE
SealXpert Cyanoacrylate Adhesive CA401 (20 grams)	812787 / 812788 / 815245 / 815246 / 815247 / 815248
SealXpert Cyanoacrylate Adhesive CA480 (20 grams)	812818 / 815253 / 815254 / 815255 / 815256 / 815257 / 815258 / 815259 / 815260 / 812789
SealXpert Cyanoacrylate Adhesive CA495 (20 grams)	812725 / 812726 / 812727 / 812728 / 812729 / 812730 / 812758 / 812771 / 812815 / 812816 / 812770 / 815240 / 815241 / 812817 / 812840
SealXpert Cyanoacrylate Adhesive CA496 (20 grams)	812721 / 812722 / 812723 / 812724 / 812759 / 812772 / 812927 / 812928 / 812929

Features:

- Available in a variety of viscosity, curing speed, gap-filling capability and substrate compatibility
- Used for fast bonding many materials such as metal, rubber, plastic, glass, leather, wood, ceramics, etc.



Product No.	Typical Use	Max Gap Fill mm	Uncured			Category	Cured		Curing Speed	
			Colour	Viscosity mPa.s	Specific Gravity g/cm³		Shear Strength Psi (kg/cm²)	Temperature Range °C (°F)	Fixture sec	Full Cure hour
CA401	General purpose, porous and acidic surface	0.10	Transparent	110	1.10	Ethyl	3,191 (224)	-55 to 83 (-67 to 181)	< 20	24
CA480	Resistant to impact and vibration, toughness	0.10	Black	250	1.10	Ethyl	3,191 (224)	-55 to 83 (-67 to 181)	< 40	24
CA495	General purpose, plastic, rubber	0.10	Transparent	45	1.05	Ethyl	2,756 (194)	-55 to 83 (-67 to 181)	< 20	24
CA496	General purpose, metal parts	0.10	Transparent	120	1.10	Ethyl	3,626 (255)	-55 to 83 (-67 to 181)	< 20	24

MAINTENANCE
SealXpert® / Wrap Seal PLUS® Repair Kit

PRODUCT NAME	IMPA CODE	PRODUCT NAME	IMPA CODE
Wrap Seal PLUS Repair Kit Complete	812330	SealXpert Maintenance and Repair Kit 1	812331
Wrap Seal PLUS Lifeboat Repair Kit 1	330287	SealXpert Maintenance and Repair Kit 2	812332
Wrap Seal PLUS Lifeboat Repair Kit 2	330288	SealXpert Maintenance and Repair Kit 3	812333
Wrap Seal PLUS Lifeboat Repair Kit 3	330289	SealXpert Maintenance and Repair Kit 4	812341
SealXpert Engineer's Repair Kit A	812235	SealXpert Maintenance and Repair Kit 5	812171
SealXpert Engineer's Repair Kit C	812237		


SealXpert® Aerosol Products

PRODUCT NAME	IMPA CODE
SealXpert SP10 Contact Cleaner (450 ml)	450592 / 450617 / 450618 / 450619 / 450621 / 450649 / 450650 / 450804 / 450805 / 450808 / 450901 / 450902 / 795510 / 795511
SealXpert SP20 Cleaner and Degreaser (450 ml)	450583 / 450616 / 450622 / 450801 / 450802
SealXpert SP30 Zinc Cold-Galvanising (Bright) (350 ml)	450587 / 450645 / 450803 / 450811 / 450812 / 450813 / 450814 / 450915
SealXpert SP40 Multipurpose Lubricant (450ml)	450420 / 450581 / 450584 / 450586 / 450591 / 450608 / 450609 / 450631 / 450702 / 450703 / 450704 / 450705 / 450709 / 450731 / 450821 / 450822 / 450823
SealXpert SP50 Moly G-Rapid (500 ml)	450514 / 450520 / 450565 / 450578 / 450606 / 450641 / 450829 / 450846 / 450847
SealXpert SP60 Silicone Grease (450 ml)	450607 / 450827 / 450828 / 450830 / 450926

Features:

- Multi-functional product, featuring in anti-rust, penetration and remove rust, lubrication, dehumidification, cleaning and corrosion prevention



SP10 Contact Cleaner	- Electronic and electrical cleaner - Grease and oil removing agent - Mould cleaner	SP40 Multipurpose Lubricant	- Stops squeaks - Loosen rusty, frozen and sticky parts - Protects against rust and metal corrosion - Removes moisture
SP20 Cleaner and Degreaser	- Heavy-duty evaporating cleaner and degreaser - Cleaning low-voltage electric motors and heavy-duty electrical and mechanical equipment while in operation	SP50 Moly G-Rapid	- Improves running-in and eliminates stick-slip - Prevents seizure for metal-to-metal contact, reduces fretting corrosion and facilitates easy disassembly - Used for pre-treatment, assembly, maintenance, repair, press-fitting and running-in of plain bearing and sliding surfaces
SP30 Zinc Cold-Galvanising (Bright)	- Repair damaged galvanised surfaces - Alternative if hot-dip galvanising is not available - Can be applied over bare steel, iron and their welds - Finish coat	SP60 Silicone Grease	- Seals, lubricates, protects, insulates and waterproofs - Safe on most rubber and plastics - Chemical, oil and water resistant - Temperature resistant

MAINTENANCE
SealXpert® RTV Silicone

PRODUCT NAME	IMPA CODE
SealXpert RV527C Clear RTV Silicone (310 ml)	812601 / 812602
SealXpert RV527W White RTV Silicone (310 ml)	812692 / 812694 / 812604 / 812605
SealXpert RV587A Blue RTV Silicone (90 grams)	812837
SealXpert RV587 Blue RTV Silicone (310 ml)	812838 / 812839
SealXpert RV596A Red RTV Silicone (90 grams)	815282
SealXpert RV596 Red RTV Silicone (310 ml)	812695 / 815283
SealXpert RV598A Black RTV Silicone (90 grams)	812841 / 815284 / 812155
SealXpert RV598 Black RTV Silicone (310 ml)	812691 / 812693 / 812842 / 812843 / 815285 / 815286 / 812156
SealXpert RV599A Grey RTV Silicone (90 grams)	812671 / 812792
SealXpert RV599 Grey RTV Silicone (310 ml)	812672 / 812793

Features:

- Low odor
- No corrosion
- Low volatility
- Weather resistance
- Chemical resistance
- Good bonding performance



RV527C Clear RV527W White	Mainly used for electric equipment selling, such as high-voltage electric switches, household electrical appliance, automobile instruments and meters (e.g. speaker).
RV587A Blue RV587 Blue	Designed for flange sealing and bonding for motive power machines, such as automobile, engineering machines, internal combustion engine, mining machines etc. which are pressing and with large gaps.
RV596A Red RV596 Red	Mainly used for sealing and bonding at high temperatures, such as steam iron, oven, engine, high temperature pipeline etc. industrial products joint surface.
RV598A Black RV598 Black	Mainly used for motive power machine, such as automotive, engineering machinery, internal-combustion, mining machinery; also can be used for joint surface sealing of water pump, valve and electrical equipment parts.
RV599A Grey RV599 Grey	Mainly used for joint surface sealing of power machines, such as reduction gears, water pump, valve and internal combustion engine etc. parts.

SealXpert® Molybdenum Disulfide Products

PRODUCT NAME	IMPA CODE
SealXpert Moly Z Powder (1.0 Kg)	450501 / 450502 / 812406 / 812407 / 812408 / 450503
SealXpert Moly Micro Powder (500 grams)	450504 / 450505 / 812401 / 812402 / 812403
SealXpert SP50 Moly G-Rapid (500 ml)	450514 / 450520 / 450565 / 450578 / 450606 / 450641 / 450829 / 450846 / 450847
SealXpert Moly 1000 Anti-Seize Compound (1.0 Kg)	450521 / 450522 / 450661 / 450662 / 450691 / 450692
SealXpert C1000 Copper Anti-Seize Compound (500 grams)	450564 / 450566 / 450635 / 450638 / 450639 / 450640 / 450633 / 450634 / 450683
SealXpert Nickel Anti-Seize (500 grams)	450598 / 450599 / 450665 / 450666 / 450681 / 450682 / 450636 / 450637 / 450693 / 450694
SealXpert Moly M77 Paste (500 grams)	450451 / 450452 / 450671 / 450672 / 450515 / 450516 / 450517 / 450518 / 450519
SealXpert Moly G-N Paste (500 grams)	450511 / 450512 / 450513 / 812411 / 812412 / 812413 / 450594 / 450595
SealXpert M (5 Litres)	450534 / 450535 / 450573 / 450574
SealXpert M-30 (1 Litre)	450536
SealXpert 111 Silicone Grease (1.0 Kg)	450756 / 450757 / 450758 / 450759 / 450551 / 450553 / 450651
SealXpert Moly Grease (500 grams)	450567 / 450568 / 450483 / 450653 / 450337
SealXpert Moly Grease (2.5 Kg)	450346 / 450481 / 450526 / 450336
SealXpert Moly Grease (15 Kg)	450347 / 450482 / 450527
SealXpert Hi-Temp Moly Grease (2.5 Kg)	450471 / 450473 / 450475 / 450761 / 450762 / 450763 / 450764 / 450732
SealXpert Hi-Speed Moly Grease (2.5 Kg)	450461 / 450463 / 450465 / 450571 / 450572
SealXpert Hi-Temp Moly Grease (15 Kg)	450472 / 450474 / 450476
SealXpert Hi-Speed Moly Grease (15 Kg)	450462 / 450464 / 450466

Features:

- Molybdenum disulfide Based
- Excellent lubricating properties at high temperature
- Good corrosion protection



MAINTENANCE
SealXpert® Molybdenum Disulfide Products

SealXpert Moly Z Powder	- As a dry burnished (rubbed-on) lubricating film for metallic contacts - As a solid lubricant additive for self-lubricating plastics and sinter metal parts, in metalworking compounds, in brake lining application
SealXpert Moly Micro Powder	- As a dry burnished (rubbed-on) lubricating film for metallic contacts - As a solid lubricant additive for self-lubricating plastics and sinter metal parts, in metalworking compounds
SealXpert SP50 Moly G-Rapid	- Improves running-in and eliminates stick-slip - Prevents seizure for metal-to-metal contact, reduces fretting corrosion and facilitates easy disassembly - Used for pre-treatment, assembly, maintenance, repair, press-fitting and running-in of plain bearing and sliding surfaces
SealXpert Moly 1000 Anti-Seize Compound	- Improves thread seal with excellent corrosion protection - Prevents seizure after prolonged exposure to high temperatures (up to 1100°C) and facilitates easy disassembly
SealXpert C1000 Copper Anti-Seize Compound	- Recommended as a protection against seizure for high temperature applications up to 1100°C - Used as protection against rust, oxidation and other corrosion, especially with dissimilar metals - Used as a rapid and easy assembly of threaded parts
SealXpert Nickel Anti-Seize	- Use on threaded parts, bushings, gears, valve systems, chain sprockets, levers, hinges, pivots, rollers, heat exchanger or manifold bolts, or as a gasket release agent - Recommended for use with stainless steel screws, flanges, nozzles, couplings and other metal fittings, or where high Nickel alloy materials such as stainless steel, or where Titanium or other hard metals are involved - For use when copper cannot be present
SealXpert Moly M77 Paste	- Suitable for lubrication points with low to moderate loads and low speeds which are subjected to water and extreme temperatures - Suitable for lubricating parts consisting of materials that are not resistant to mineral oils and is used on metal-to-metal parts with frictional and contact surfaces, brake anchor plates and the brake pistons of disc brakes
SealXpert Moly G-N Paste	- Prevents frictional corrosion and scoring, offers protection from stick-slip and has good anti-corrosion properties - Recommended as a running-in lubricant for new machines and gear-boxes, and press-fit production of all types of machine elements
SealXpert M	Recommended as an additive to mineral-based lubricating, engine and gear oils in circulating and splash lubrication system and gearboxes
SealXpert M-30	Recommended as an additive to mineral-based lubricating, engine and gear oils in circulating and splash lubrication system and gearboxes
SealXpert 111 Silicone Grease	- Recommended for long-term lubrication of valves, stop cocks, plug cocks, 'O' rings, valve/lip seals, packings, gaskets - Suitable for vacuum and pressure systems
SealXpert Moly Grease	Suited to a wide range of applications, including bearings, gears, and sliding parts.
SealXpert Hi-Temp Moly Grease	Recommended for extreme high temperatures required at ironworks, cement plants, etc. for sliding; rotating and threaded parts in steel mill sliding nozzles and rotary nozzles, bearings in ladle hangers and furnace dampers; transfer surfaces of tire liners and support rollers in rotary kilns at cement plants; sliding parts, bolts, nuts, pins, and bushings under high temperature
SealXpert Hi-Speed Moly Grease	- Recommended for use on bearings in electric machinery designed to reduce energy and current usage, and on high speed conveyance linear motion devices and ball screws - Use on machine tool spindles and other bearings that revolve at high-speeds

FIRE PROTECTION
SealXpert® FlameCease FC100 Fire Protection Coating

PRODUCT NAME	IMPA CODE
SealXpert FlameCease FC100 Fire Protection Coating (20 Kg)	812232

Features:

- Low installation cost
- High Durability Fire Tested under British Standard 476 Part 6, 7 and 20
- Contains no halogenated flame retardant
- Excellent lap shear, tensile and compressive strengths
- More specific to address complex issues with different resin types

Technical data:

Heat distortion temperature	: 117 °C (243 °F)@ 264 psi (19 kg/cm²)
Peak exotherm temperature	: 174 °C (345 °F)
Gel time	: 15 min
Gel to peak exotherm	: 18 min
Total time to peak exotherm	: 28 min
Barcol hardness	: 49
Tensile strength	: 6,672 psi (469 kg/cm²)
Tensile modulus	: 73 x 10 ⁹ pa
Flexural strength	: 23,931 psi (1,683 kg/cm²)
Flexural modulus	: 6.8 x 10 ⁹ pa
Adhesive strength	: 1,958 psi (138 kg/cm²)
Tensile elongation	: 2.8%



Seal
xpert
SealXpert® Products



mailbox@sealxpert.com
www.sealxpert.com

